

# LumosCielo™

Standardized square and rectangle luminous ceiling panels offer a modern and adaptable solution for enhancing indoor lighting. These geometric luminous panels provide uniform illumination, making them ideal for various settings.

Static CCT 2700K / 3000K / 3500K / 4000K / 5000K / 5700K  
with 0-10 Dimming and RF-Remote / Tunable White



## Benefits

### Uniform illumination:

LumosCielo™ luminous panels provide consistent, even lighting throughout the space, improving visibility and ambience.

### Easy installation and maintenance:

The panels are simple to install and maintain, making them a great choice for residential, commercial and industrial settings.

### Energy-efficient:

LumosCielo™ luminous panels are designed to be energy-efficient, helping you to save on your energy costs.

### Sleek and modern design:

LumosCielo™ luminous panels have a sleek modern design that complements any space.



Surface Mounted



Suspended



Recessed



bridgelux®

CRI > 90



160°





## Static CCT Standard Output

## Static CCT High Output

SIZE	Total Power	Total Luminous Flux		SIZE	Total Power	Total Luminous Flux
4'x4'	168 W	13440 lm		4'x4'	218.4 W	17472 lm
6'x4'	252 W	20160 lm		6'x4'	327.6 W	26208 lm
8'x4'	324 W	25920 lm		8'x4'	436.8 W	34944 lm
5'x5'	280.8 W	22464 lm		5'x5'	367.2 W	29376 lm
6'x6'	378 W	30240 lm		6'x6'	504 W	40320 lm
6'x8	504 W	40320 lm		6'x8	672 W	53760 lm

## Tunable White Standard Output DMX Control

## Tunable White High Output DMX Control

SIZE	Total Power	Total Luminous Flux		SIZE	Total Power	Total Luminous Flux
4'x4'	168 W	13440 lm		4'x4'	218.4 W	17472 lm
6'x4'	252 W	20160 lm		6'x4'	327.6 W	26208 lm
8'x4'	324 W	25920 lm		8'x4'	436.8 W	34944 lm
5'x5'	280.8 W	22464 lm		5'x5'	367.2 W	29376 lm
6'x6'	378 W	30240 lm		6'x6'	504 W	40320 lm
6'x8'	504 W	40320 lm		6'x8'	672 W	53760 lm

# Specification Code Generator

LCLC	-	-	-	-	-	12	-	-	-	LU
<b>Company</b>	<b>Shape</b>	<b>Dimension</b>	<b>CCT</b>	<b>Output</b>	<b>Control</b>	<b>Profile</b>	<b>Profile Color</b>	<b>Mounting</b>	<b>System</b>	
<input type="checkbox"/> LumosCielo™ <input type="checkbox"/> Product <input type="checkbox"/> LumosCielo™	<input type="checkbox"/> Square <input type="checkbox"/> Rectangle	<input type="checkbox"/> 4'x4' <input type="checkbox"/> 6'x4' <input type="checkbox"/> 8'x4' <input type="checkbox"/> 5'x5' <input type="checkbox"/> 6'x6' <input type="checkbox"/> 6'x8'	<input type="checkbox"/> 2700K <input type="checkbox"/> 3000K <input type="checkbox"/> 3500K <input type="checkbox"/> 4000K <input type="checkbox"/> 5000K <input type="checkbox"/> 5700K <input type="checkbox"/> Tunable	<input type="checkbox"/> Standard <input type="checkbox"/> High	<input type="checkbox"/> No dimming <input type="checkbox"/> 0-10V <input type="checkbox"/> Dali <input type="checkbox"/> DMX	<input type="checkbox"/> 120	<input type="checkbox"/> Clear <input type="checkbox"/> White <input type="checkbox"/> Black	<input type="checkbox"/> Surface <input type="checkbox"/> Suspended <input type="checkbox"/> Recessed	<input type="checkbox"/> Lumosanti	

Example: LCLC-SQ-48"x48"-57-ST-DM-12-CL-SF-LU

Our tool is designed for architects and lighting designers to simplify the process of incorporating our lighting products into their designs. This tool helps create a specification code tailored to meet project needs, ensuring that they are, in line with industry standards.

By entering details such as frame dimensions, color temperature, profile, profile color and mounting type, users can generate codes that reflect their design preferences. This will reduce mistakes and facilitate smooth communication with us and contractors.

